

# Cylinder Dimensions

by

## Precision Model Distributors

<b>Bore Ø</b>	<b>K</b>	7 mm	9 mm	12 mm	14 mm	16 mm
<b>Fitting Thread</b>		M3	M3	M3	M4	M4
<b>Piston Rod Diameter</b>	<b>A</b>	3 mm	4 mm	6 mm	6 mm	8 mm
<b>Outer Case Diameter</b>	<b>B</b>	11 mm	14,1 mm	16,5 mm	17,8 mm	21 mm
<b>Center Section Diameter</b>	<b>C</b>	9,5 mm	13,1 mm	15,5 mm	17 mm	20 mm
<b>Eye O.D.</b>	<b>D</b>	8 mm	8 mm	8 mm	8 mm	12 mm
<b>Base Tang Bore I.D.</b>	<b>E</b>	3 mm	4 mm	4 mm	4 mm	4 mm
<b>Eye I.D.</b>	<b>H</b>	3 mm	4 mm	4 mm	4 mm	6 mm
<b>Standard (Grundmaß)</b>		33 mm	37 mm	39,5 mm	40,5 mm	45 mm
<b>Closed Eye to Eye</b>	<b>L2=</b>	33 mm + Stroke (Hub)	37 mm + Stroke (Hub)	39,5 mm + Stroke (Hub)	40,5 mm + Stroke (Hub)	45 mm + Stroke (Hub)

Cylinders available in strokes of 25, 50, 75 and 100mm

